
Threaded Sealing Plugs with assembled washer

Threaded sealing plug design EP 435 complete with washer provides an outstanding seal force useable under complicated working conditions









DIN EN ISO 228-1 / DIN 3852-2

All dimensions in mm

Thread		Total height		Snonnor				
Size	Flange	Thread Length	Head Length	Spanner Size	Washer		Туре	Reference No.
d ₁	D	L₁	L ₂	sw	Т	R		
G 1/8	16.8	7.5	11.2	13	1.0	18.0	Α	EP 4371/8"
G 1/4	19.0	7.5	11.3	13	1.0	20.5	Α	EP 4371/4"
G 3/8	22.0	7.6	12.5	17	1.0	23.5	Α	EP 4373/8"
G 1/2	27.0	10.6	14.7	19	1.0	28.5	Α	EP 4371/2"
G 3/4	32.2	10.5	14.2	24	1.0	33.5	Α	EP 4373/4"
G 1	39.7	13.6	15.8	27	1.0	41.0	В	EP 437 – 1."
G 1 1/4	49.8	13.5	17.8	36	1.0	51.5	В	EP 437 - 1.1/4"
G 1 1/2	55.4	13.5	16.5	41	1.0	56.5	В	EP 437 – 1.1/2"
G 2	68.2	13.5	16.9	55	1.0	73.0	В	EP 437 – 2."

Material:

Premium, impact resistant Nylon (PA 6)

Standard Colour:

yellow

Threaded sealing plug design EP 435 complete with washer provides an outstanding seal force useable under complicated working conditions.



Metric DIN 3852-1 / DIN ISO 6149-1

All dimensions in mm

M 10 × 1	14.0	5.5	11.5	10	1.0	16.5	В	EP 437 – M 10 × 1
M 12 × 1.5	17.2	8.2	11.5	13	1.0	19.5	Α	EP 437 – M 12 × 1.5
M 14 × 1.5	19.1	10.1	11.2	13	1.0	22.7	Α	EP 437 – M 14 × 1.5
M 16 × 1.5	21.7	7.5	11.6	17	1.0	24.5	Α	EP 437 – M 16 × 1.5
M 18 × 1.5	23.8	8.6	12.3	17	1.0	26.5	Α	EP 437 – M 18 × 1.5
M 20 × 1.5	25.8	8.5	15.5	19	1.0	28.7	Α	EP 437 – M 20 × 1.5
M 22 × 1.5	26.7	8.6	15.5	19	1.0	29.5	Α	EP 437 – M 22 × 1.5
M 24 × 1.5	31.2	10.6	15.2	24	1.0	32.5	Α	EP 437 – M 24 × 1.5
M 26 × 1.5	31.8	8.5	15.5	24	1.0	33.6	Α	EP 437 – M 26 × 1.5
M 27 × 2	32.1	11.5	15.4	24	1.0	33.5	Α	EP 437 – M 27 × 2
M 33 × 2	39.6	11.5	15.6	27	1.0	41.5	В	EP 437 – M 33 × 2
M 42 × 2	49.8	11.5	16.6	36	1.0	51.0	В	EP 437 – M 42 × 2

Should your requirements not be shown please ask for a separate quotation. SEALWELL products and specifications are subject to improvement and change without notice.

Threaded Sealing Plugs with assembled washer

Threaded sealing plug design EP 435 complete with washer provides an outstanding seal force useable under complicated working conditions

TRIPLE ADVANTAGE of CAPTOP

QUALITY. Nylon 6 is used for its stability to withstand temperatures of up to 150°C and pressures up to 2,5 bar (during painting processing and testing). Five complete threads for optimum use. The hexagon head allows tightening and removal with either a screwdriver or a spanner or special tool Guaranteed seal. Nylon 6 guarantees a very high resistance against hydraulic fluids, acids, base alkalines and Solvents. Extremely economical when compared to metal.

AVAILABILITY. With over 400 million moulded components shipped from our Oststeinbek / Hamburg logistics center we provide the fastest on time delivery service to all markets and industries.

PHILOSOPHY. Innovative protective closures at the best price in the market.





ISO 11926-1

All dimensions in mm

Thread		Total height		Cnannar							
Size	Flange	Thread Length	Head Length	Spanner Size	Washer				Туре	Reference No.	
d₁	D	L ₁	L_2	SW	Т	R					
7/16 – 20 UNF	21.0	10.0	10.2	13	1.0	22.0	Α	EP 4377/16" - 20 UNF			
1/ 2 – 20 UNF	22.8	9.6	11.3	13	1.0	24.0	Α	EP 4371/ 2" - 20 UNF			
9/16 – 18 UNF	24.8	9.5	11.3	13	1.0	26.0	Α	EP 4379/16" - 18 UNF			
5/ 8 – 18 UNF	24.9	10.5	13.2	17	1.0	26.0	Α	EP 4375/ 8" - 18 UNF			
3/ 4 – 16 UNF	25.6	8.9	14.3	17	1.0	27.0	Α	EP 4373/ 4" - 16 UNF			
7/ 8 – 14 UNF	33.9	12.5	13.6	19	1.0	35.0	Α	EP 4377/ 8" - 14 UNF			
1 1/16 – 12 UN	40.7	12.5	13.4	24	1.0	42.0	Α	EP 437 – 1.1/16" – 12 UN			
1 5/16 – 12 UN	42.1	13.5	16.5	27	1.0	43.0	Α	EP 437 – 1.5/16" – 12 UN			
1 5/ 8 – 12 UN	55.6	15.7	16.3	36	1.0	59.0	Α	EP 437 – 1.5/ 8" – 12 UN			
1 5/ 8 – 16 UN	57.6	15.8	16.6	36	1.0	59.0	Α	EP 437 – 1.5/ 8" – 16 UN			

Should your requirements not be shown please ask for a separate quotation. SEALWELL products and specifications are subject to improvement and change without notice.

Material:

Premium, impact resistant Nylon (PA 6)

Standard Colour : yellow

yellow

Individual Productions:

On request we develop and produce individually tailored solutions next to the standard items of this range: additional dimensions, different materials and new colours

We would be pleased to advise you.

