PROTEC PROSICON® EPS 175







YOUR PROSICON® PRODUCT ADVANTAGE. BEST PRICE PERFORMANCE IN THE MARKET.

HIGH TEMP SILICONE PLUGS WITH HANDLES.

Conical shaft, tapered to fit into a range of hole sizes, without collar. Lightweight construction with hollow core.

Central pull tab for easy and quick insertion and removal.

Recommended for Powder coating, e-coating, plating & anodizing.

PREMIUM SILICONE MATERIAL PROPERTIES.

Prosicon® Silicone rubber 55 shore A withstands temperatures up to max. 316 $^{\circ}$ C / 4 hours. On request also in EPDM material up to max. 177 $^{\circ}$ C available.

PROSICON® BLU SIGNATURE® PRODUCT CODE.

Premium. Reusable. Stabilized with Special Blends.

COLOR OPTIONS.

Natural. Also available in colour coding.

TECHNICAL CLEANLINESS FOR ACCURATE MASKING.

Prosicon® Silicone Maskign Caps and Plugs are stabilized and tempered separately. This process improves dimensional stability and prevents plasticizer exudation during customer applications under high temperature conditions.

PREMIUM SILICONE MATERIAL PROPERTIES.

Prosicon® Silicone Maskign Caps and Plugs have an excellent resistance to high temperature, chemicals and acids and can be used several times without loss of quality



MATERIALS SELECTION GUIDE.

EPDM rubber, Neoprene, NBR rubber, SBR, TPE, ecc.

APPLICATION.

High Temperature Masking Caps and Plugs to protect your product during finishing processes like powder coating, KTL, Wet painting, anodizing, electroplating and e.coating treatments. Extremely temperature resistant up to 316° C, robust, versatile and time-saving in application.

SILICONE / EPDM CUSTOM DESIGN AT RECORD SPEED.

We develop your individual parts that are not listed or alternative dimensional designs of this range that are tailored to your requirements.

Customized. For your special application


Time Saver. Rapid Prototyoing & Hi-Speed functional samples


Hi-Speed. Fast Lane Serial Mold Construction Unbeatable. At the best price in the market

PROTEC PROSICON® EPS 175

€ sealwell

High Temp Silicone Plugs with Handles





DIMENSIONSAll dimensions in mm

Dimensions					Colon	Chave A	Standard	Deference No.
d_1	d ₂	h ₁	н	D	Color	Shore A	Pack	Reference No.
0.79	3.18	15.88	25.40	3.18	natural	60	1.000	EPS 175 / 125-H
1.60	3.18	15.88	25.40	3.18	light green	60	1.000	EPS 175 / 125- 625-H
1.60	4.75	15.88	25.40	3.18	pink	60	1.000	EPS 175 / 187- 625-H
3.18	6.35	19.05	31.75	3.18	black	55	1.000	EPS 175 / 250- 750-H
4.75	8.71	15.88	28.58	4.75	dark red	55	500	EPS 175 / 343- 625-H
6.35	9.53	12.70	25.40	5.08	white	55	500	EPS 175 / 375- 500-H
6.35	9.53	19.05	31.75	6.35	yellow	55	250	EPS 175 / 375- 750-H
8.74	11.91	20.65	38.10	7.00	N.N.	50	100	EPS 175 / 469- 813-H
10.31	15.09	25.40	44.45	8.00	violet	50	100	EPS 175 / 594-1000-H
11.13	15.88	22.23	41.28	5.94	light green	50	100	EPS 175 / 625- 875-H
12.70	16.66	25.40	44.45	6.35	pink	50	100	EPS 175 / 656-1000-H
15.88	19.84	25.40	44.45	7.24	red	50	100	EPS 175 / 781-1000-H
18.26	23.83	25.40	44.45	7.62	yellow	50	100	EPS 175 / 938-1000-H
19.05	25.40	25.40	44.45	7.62	natural	50	100	EPS 175 / 1000-1000-H

Should your requirements not be shown please ask for a separate quotation. SEALWELL products and specifications are subject to improvement and change without notice.