PROTEC PROSICON° EPS 400

High Temp Masking Silicone Combi Plugs





YOUR PROSICON® PRODUCT ADVANTAGE. BEST PRICE PERFORMANCE IN THE MARKET.

HIGH TEMP MASKING SILICONE COMBI PLUGS.

The ideal plug for protecting metric internal threads and threaded holes, also suitable for protecting assembly holes.

Conical shaft design. All-purpose stopper that can be used on both sides. Central pull tab. Optimal press fit achieves a high sealing effect. Recommended for Powder coating, e-coating, plating & anodizing.

PREMIUM SILICONE MATERIAL PROPERTIES.

Prosicon[®] Silicone rubber 55 shore A withstands temperatures up to max. 316 ° C / 4 hours. On request also in EPDM material up to max. 177 ° C available.

PROSICON® BLU SIGNATURE® PRODUCT CODE.

Premium. Reusable. Stabilized with Special Blends.

COLOR OPTIONS.

Special color runs available on request.

TECHNICAL CLEANLINESS FOR ACCURATE MASKING.

Prosicon[®] Silicone Maskign Caps and Plugs are stabilized and tempered separately. This process improves dimensional stability and prevents plasticizer exudation during customer applications under high temperature conditions.

PREMIUM SILICONE MATERIAL PROPERTIES.

Prosicon[®] Silicone Maskign Caps and Plugs have an excellent resistance to high temperature, chemicals and acids and can be used several times without loss of quality.



MATERIALS SELECTION GUIDE.

EPDM rubber, Neoprene, NBR rubber, SBR, TPE, ecc.

APPLICATION.

High Temperature Masking Caps and Plugs to protect your product during finishing processes like powder coating, KTL, Wet painting, anodizing, electroplating and e.coating treatments. Extremely temperature resistant up to 316° C, robust, versatile and time-saving in application.


SILICONE / EPDM CUSTOM DESIGN AT RECORD SPEED.

On request we develop and produce individually tailored solutions along with the standard items of this range: If you require additional dimensions, different materials and new colours. We would be pleased to assist you.

Customized.	For your special application
Time Saver.	Rapid Prototyoing & Hi-Speed functional samples
Hi-Speed.	Fast Lane Serial Mold Construction
Unbeatable.	At the best price in the market

PROTEC PROSICON° EPS 400 High Temp Masking Silicone Combi Plugs





DIMENSIONS

All	dimer	nsions	in	mm
7 111	annoi	1010110		

dı	d ₂	d ₃	h1	h ₂	Metric	Shore A	Color	Std. Pack	Reference No.
2.00	3.50	2.50	6.50	13.00	M 3	55	blue	1.000	EPS 400 / M3
3.75	4.30	3.40	6.50	20.00	M 4	55	yellow	1.000	EPS 400 / M4
4.20	5.20	4.30	7.50	20.50	M 5	55	black	1.000	EPS 400 / M5
5.75	7.35	5.10	7.50	23.00	M 6	55	green	1.000	EPS 400 / M6
7.00	12.50	7.00	10.00	23.60		55	pink	500	EPS 400 / 0276
7.75	8.90	6.90	10.00	23.00	M 8	55	orange	500	EPS 400 / M8
7.93	12.50	7.10	70.00	23.40		55	red	500	EPS 400 / 0280
9.00	10.50	8.50	13.00	25.00	M 10	55	blue	500	EPS 400 / M10
10.30	12.30	10.50	14.5	25.00		55	grey	250	EPS 400 / M12

Should your requirements not be shown please ask for a separate quotation.

SEALWELL products and specifications are subject to improvement and change without notice.